



Rope Light ILMÉX-LED Transparent Tube


Ref. **007004.1...**

Horizontal LED Smooth Surface

Size: Ø13mm x 51m
 Cutting Unit: 1,5m
 No. Led: 36 LEDs/m
 Led Spacing: 27,7mm
 Voltage: 220-240V/50Hz
 Power: 3,12W/m
 Extendable: 102m
 LED Colours: ○●●●●●●●●●●


Brightness Angle
 -ILMÉX Optimal Brightness Angle

320°



Pack: 51m/9,15kg/34x34x17cm

Conical LED horizontally inserted



-Horizontal LED will provide more brightness
 -Distance between LEDs is 27,7mm

LED	Reference
	007004.1.TW
	007004.1.TB
	007004.1.TPU
	007004.1.TP
	007004.1.TWW
	007004.1.TA
	007004.1.TY
	007004.1.TO
	007004.1.TR
	007004.1.TG


Accessories (more on page 127)

Power cord with plug included

Length: 1,5m
 Voltage: 220-240V/50Hz
 Current: 2A
Grey Wire



Zone	Reference
Europe	0082005.1.GR
United Kingdom	0082011.1.GR
France	0082015.1.GR





Rope Light ILMÉX-LED Colour Tube

Ref. **007003.1...**


Size: Ø13mm x 51m
 Cutting Unit: 1,5m
 No. Led: 36 LEDs/m
 Led Spacing: 27,7mm
 Voltage: 220-240V/50Hz
 Power: 3,12W/m
 Extendable: 102m
 LED Colours: ○●●●●●●●

 Pack: 51m/9,15kg/34x34x17cm


Horizontal LED Smooth Surface

Brightness Angle
 ·ILMÉX Optimal Brightness Angle










320°



Conical LED horizontally inserted



·Horizontal LED will provide more brightness
 ·Distance between LEDs is 27,7mm

LED	Reference
	007003.1.WW
	007003.1.BB
	007003.1.PUPU
	007003.1.PP
	007003.1.AA
	007003.1.YY
	007003.1.OO
	007003.1.RR
	007003.1.GG

Accessories (more on page 127)

Length: 1,5m
 Voltage: 220-240V/50Hz
 Current: 2A
Grey Wire

Power cord with plug included



Zone	Reference
Europe	0082005.1.GR
United Kingdom	0082011.1.GR
France	0082015.1.GR



Accessories for ILMÉX-LED Rope Light


Easy Assembly
Professional Finish



Rope Light is provided with cutting units to join the required meters and cover the desired area (not exceeding the maximum extendable meters shown in the data sheet). Below you will find the most common accessories for these connections. In case of LED rope light, power cord is provided with an AC/DC rectifier as shown below. These accessories are valid for the different LED Rope light models described in previous pages.


Ref. _____ Power cord with plug

Europe: **0082005.1.GR**
U.K: **0082011.1.GR**
France: **0082015.1.GR**
Length: **1,5m**
Voltage: **220-240V/50Hz**
Current: **2A**
Green/Grey Wire




Ref. _____ Power cord w/o rectifier or plug


2082008.GR/ Length: 0,5m
2082009.GR/ Length: 1m
2082010.GR/ Length: 1,5m
2082020.GR/ Length: 3m
Grey Wire




_____ Extension wire ILMÉX-LED



Ref. 2082014 _____ L Connector




Ref. 2082015 _____ X Connector




Ref: **2082005.GR/ Length: 0,5m**
Ref: **2082006.GR/ Length: 1m**
Ref: **2082007.GR/ Length: 1,5m**
Ref: **2082021.GR/ Length: 3m**
Grey Wire


Ref. 2082011 _____ Mounting clip




Ref. 3820700 _____ Polycarbonate U Profile




Ref. 2082012 _____ Suction pad




Ref. 2082004 _____ Transparent shrinkable tube




Ref. 2082003 _____ End Cap



Ref. 2082002 _____ Easy Splice Connector



Ref. 2082013 _____ T Connector



Ref. 2082016 _____ Linear connector outdoor

